

ADICIONAR REPOSITÓRIOS NÃO OFICIAIS PFSENSE

CONEXTI – SOLUÇÕES EM TI LTDA

RUA DO COMÉRCIO, 525, EDIFÍCIO ÂNGELO SPRICIGO – SALA 301 CONCÓRDIA-SC – CEP: 89700-000 +55 (49) 3442-3747 conexti.com.br sys-squad.com goxdrive.com.br

- 1. Instalando System_Paches.
- 1.1. O System Patch é o pacote responsável por gerenciar os paches dentro do pFsense, para instala-lo basta acessar o gerenciador de pacotes e busca-lo.

System / Package Manager / Available Packages							
Installed Packages	Available Packages						
Search			•				
Search term	system_patch	Both Clear					
	Enter a search str	ing or *nix regular expression to search package names and descriptions.					
Packages							
Name	Version	Description					
System_Patches	1.2_1	A package to apply and maintain custom system patches.	tall				

2. Acessando o System Patches.

	System -	Interfa	ces 🕶	Firewall -	Services -	VPN -	Status 🕶	Diagnostics -	Help 🕶				€
WARNING: The	Advanced Cert. Manage	er	l is set to	the default valu	Je. Change the pa	assword in th	e User Manage	r.					
System /	General Setup High Avail. Sync Logout (admin)												0
This page allow Use with cautio	Package Ma Patches	nager	rom the o	fficial code repo	ository or pasted	in from e-ma	il or other sour	ces.					×
System Pato	Routing Setup Wizard	I											
Descrip	User Manage	er						Fetc	h Test	Apply	Revert	Auto Apply	Actions

- 3. Configurando um Patch.
- 3.1. Para adicionar um novo patch basta clicar em "Add New Patch"

System / Patches	s/ Edit	0
Patch Details		
Description	patch_pacotes_unofficiais Enter a description here for reference.	
URL/Commit ID	Enter a URL to a patch, or a commit ID from the main github repository (NOT the tools or packages repos!)	
Patch Contents	<pre> /etc/inc/pkg-utils.orig 2018-09-24 17:51:32.458825000 -0300 +++ /etc/inc/pkg-utils.inc 2018-09-24 17:51:54.387033000 -0300 @@ -388,7 +388,7 @@ if (base packages) {</pre>	
Patch Application Be	havior	
Path Strip Count	1 ▼ The number of levels to strip from the front of the path in the patch header.	
Base Directory	/ Enter the base directory for the patch, default is /. Patches from github are all based in /. Custom patches may need a full path here such as /usr/local/www/.	
Ignore Whitespace	Ignore whitespace in the patch.	

Coloque alguma descrição para identificar o patch e no campo "Patch Contents" deve ser posto o conteúdo do link (<u>https://github.com/marcelloc/Unofficial-pfSense-packages/blob/master/244_unofficial_packages_list.patch</u>), deixe os outros parâmetros como na imagem a cima e em seguida, salve.

3.2. Teste o novo patch.

Syste	em / Patches						0
Patch c Patch c	an be applied cleanly (detail) an NOT be reverted cleanly (detail)						×
Syster	m Patches						
	Description	Fetch	Test	Apply	Revert	Auto Apply	Actions
□ .‡.	patch_pacotes_unofficiais		✓ Test	Apply		No	e 🖉
				+ Add N	lew Patch	💼 Del	ete Patches

3.3. Teste(Test) e aplique(Apply) o novo patch.

Syst	em / Patches						Ø
Patch a	applied successfully						×
Syste	m Patches						
	Description	Fetch	Test	Apply	Revert	Auto Apply	Actions
■. ‡ .	patch_pacotes_unofficiais		✔ Test		Revert	No	D 🗊
				+ A	dd New Patch	<u>Î</u> Del	ete Patches

Após esse procedimento os pacotes extra oficiais já poderão ser encontrados e disponíveis para instalação.